



# Temporis





## IP Extension Module



### An intuitive tool to enhance call handling

- The Temporis IP Extension Module **extends the capabilities of Temporis IP800.**
- **Ideal for administrative assistants, receptionists and workers** who have to monitor, manage and cover call status.
- Make it your own. **Configure the keys to meet your specific needs:** BLF, BLA, XML browser, line or speed dial keys and many more.
- Benefit from a **large graphic display with easy-to-understand icons and dual color LED keys** to know line status at a glance.
- Install it to suit you thanks to the **adjustable 2-position foot stand.**

#### EXTRA

-  Large graphic display
-  Dual color LED keys
-  Up to 38 function keys
-  6 Temporis IP Extension Modules can be daisy chained

## Temporis IP Extension Module

Commercial reference  
3 700 601 401 943



### Main features

- 160x320 graphic display with 4-level gray scales
- LCD icons dedicated to each programmed function
- Dual color LED for status information
- Supports Busy Lamp Field (BLF), Bridge Line Appearance (BLA), speed dial, call pick up, intercom, call park, directory (local or network), LDAP, XML browser, voicemail, call forward, DND...

### Key pad

- 20 physical keys
- Up to 38 keys thanks to page switch function
- Dual color LED buttons (green/orange)

### Interfaces

- 2 RJ-12 ports (data in and out)

### Supported phones

- Temporis IP800

### Physical & Environmental

#### Mounting:

- Adjustable footstand: 2 positions

#### Power Supply:

- Temporis IP Extension Module is powered directly by Temporis IP800 for up to two daisy-chained modules.
- When more than 2 extension modules (up to 6) are required a power adaptor is needed.

#### Power Adaptor: not provided

- Input: AC 100/240V
- Output: 5V/3A

#### Dimensions:

- 192x120x45mm (HxLxD)

#### Operating temperature:

- From 0° to 40°C

#### Storage temperature:

- Up to 60° C

#### Humidity:

- Up to 90% non-condensing



[www.atlinks.com](http://www.atlinks.com)